

# K SERIES

## MULTITUBULAR HEAT EXCHANGER



The K series heat exchanger is an all stainless steel shell and tube heat exchanger for industrial use. The product to be heated or cooled flows through the interior tubes. The media fluid flows through the surrounding shell. The K series is the ideal heat exchanger for steam to water applications such as CIP heating. Corrugated tubes are used to increase heat transfer rates which makes the K series much more efficient than normal smooth tube heat exchangers.

### APPLICATIONS:

Low to medium viscosity fluids.  
Industrial applications.  
CIP heating.

### MATERIALS:

Shell side: AISI 304 stainless steel.  
Tube side: AISI 316L stainless steel.

### CONNECTIONS:

Shell side: DIN flange.  
Tube side: Tubeplate-DIN flange

### FINISHING:


Shell side: Polished  
Tube side: Unpolished.

### DESIGN CONDITIONS:

Shell side: 10 barg / 185 °C.  
Tube side: 10 barg / 185 °C.



An expansion bellow is fitted in the outer shell for absorbing the differential expansion between the shell and the inner tube.



For large duties, multiple units can be interconnected and mounted in a frame.

### RANGE:

Models:	Lengths (m)	Surface area (m <sup>2</sup> )	Shell side Connection	Tube side Connection	Max flow shell (m <sup>3</sup> /hr)	Max flow tubes (m <sup>3</sup> /hr)	Volume shellside (L)	Volume tubeside (L)
K 4 64/18	0,7 – 6,0	1,4	DN32	DN50	8	11	11,1	4,8
K 7 76/18	0,7 – 6,0	2,3	DN40	DN65	16	13	17,7	8,3
K 13 104/18	0,7 – 6,0	4,3	DN65	DN80	40	24	31,5	15,4
K 19 129/18	0,7 – 6,0	6,3	DN80	DN100	55	35	50,7	22,6
K 37 168/18	0,7 – 6,0	12,3	DN80	DN150	55	67	82,0	44,0
K 55 219/18	0,7 – 6,0	18,4	DN125	DN200	130	100	145,4	65,3

The following lengths can be supplied: 0,7 / 1,0 / 1,5 / 2,0 / 3,0 / 6,0  
The surface area and volumes shown are for 6,0 meter lengths models.

To find out more about HRS Heat Exchangers contact us at:

©2010 HRS Heat Exchangers.  
All rights reserved.

Tel: +34 968 201 488  
Fax: +34 968 200 461

www.hrs.heatexchangers.com  
info@hrs-heatexchangers.com